

ACCESSORIES

I-COM SERIES UPS ACCESSORIES



MODEL: RMP-X1

UPS Remote Monitoring Panel



- Touchscreen TFT display
- RS485 input port (for long distance)
- RS232 input port
- RS232 output port + dry contact port
- Emergency stop input
- Functional desktop and wall-mount design

MODEL: SNMP

External SNMP Adaptor for UPS



- WEB based monitoring & management
- SNMP management
- Multi server shutdown
- Multi UPS monitoring

MODEL: US-4 & US-8

UPS Multiserver Shutdown Unit



- RS232 giriş portu
- RS232 çıkış
- 4 veya 8 çoğaltılmış kuru kontak çıkışı

MODEL: RSX24

External RS232 to RS485 Converter for UPS and STS



- For long distance communication
- Bi-directional operation
- 4 wire RS485 output (Half & full duplex)

MODEL: ML100

Serial Port Multiplexer for UPS and STS



- RS232 input port
- 2 x DB9 type socket RS232 outputs
- External or internal

MODEL: RS-NET

External RS232 to TCP/IP Converter for UPS and STS



- Monitoring & management over TCP/IP

MODEL: ML200

Internal Serial port multiplexer for UPS and STS



- RS232 input port
- DB9 type socket RS232 output
- RJ45 Ethernet output (TCP/IP)

ACCESSORIES

I-COM SERIES UPS ACCESSORIES



MODEL: MDX2

External MODBUS over RS485 adaptor for UPS and STS



- For SCADA and BMS connection
- MODBUS RTU protocol
- 2 wire RS485 output
- 8 bit hardware addressable

MODEL: GM-2

UPS için Harici GSM / GPRS Modem



- SMS option
- Monitoring & management via GPRS and SMS
- Directly UPS connection
- Smart modem
- Push-push SIM card installation
- Easy configuration by the Utility PC software

MODEL: MDX-NET

External MODBUS over TCP/IP Adaptor for UPS and STS



- For SCADA and BMS connection
- MODBUS TCP protocol
- RJ45 Ethernet output
- 8 bit hardware addressable

MODEL: GM3

External GSM / GPRS Modem for UPS with Internal Battery Unit



- SMS option
- Monitoring & management via GPRS and SMS
- Directly UPS connection
- Smart modem
- Push-push SIM card installation
- Easy configuration by the Utility PC software
- Uninterruptible communication with internal battery

MODEL: GM-1

External GSM modem for UPS



- For SMS option
- SNMP compability
- Control via AT commands
- Configuration by the SNMP web interface
- Push-push SIM card installation

MODEL: GMB1

External Battery Unit for GM-2 Modem



This unit is the external battery bank for GM-2 modem